

# D/A (DIGITAL-TO-ANALOG) CONVERTER SPECIFICATIONS

**E-Mon D-Mon<sup>®</sup>**  
Metering Products & Systems

**Test Equipment  
Depot**  
1-800-517-8431

## DESCRIPTION

The D/A (digital-to-analog) converter module is used along with the E-Mon D-Mon<sup>®</sup> Class 2000 meter(s) to interface with analog meters, chart recorders, meter relays, and programmable controllers.

## D/A CONVERTER SPECIFICATIONS

Input Voltage:	120 VAC, 60 Hz
Available Outputs:	0-10 volts dc (at 10 mA maximum)
	0-1 mA (into load of 0-10K ohms)
	4-20 mA (into load of 0-250K ohms)
Operating Temperature:	0 degrees C to 60 degrees C
Dimensions:	6 3/4" H x 3 3/4" W x 3 1/4" D



## ORDERING INFORMATION

When ordering, state model number of the E-Mon D-Mon meter that will be used with the D/A converter. (e.g., 208200 KIT, 480400D KIT)

State output required from D/A converter (choose one):

- 0-10 Vdc
- 0-1 mA
- 4-20 mA

Test Equipment Depot - 800.517.8431 - 99 Washington Street Melrose, MA 02176  
FAX 781.665.0780 - TestEquipmentDepot.com

**E-Mon<sup>®</sup>**

Effective Date 6/1/2006